BUS:			CELL:		JLI	VICE MUVIOUN	, , , , , , , ,	MILEAGE	IN / OUT	I TAG
	COLOR YEAR MAKE/MODEL		VIN		LICENSE	MILEAGE	114 / 00 /			
•	22	FOR	D F-150 B	BEV	1FTV	W1EL6NWG0518	7		62475 I INV. [	T1692
DEL. DATE			WARR, EXP.	PROMIS	ED	PO NO.	RATE	PAYMENT	INV. L	JATE
310CT25 IS 310CT25 DI			310CT2025	10.00 2	ENOV25			CASH	25NOV2	25
R.O. OPEN			READY	OPTIONS	DI 1	R:00845 ENG:	Battery I	Electric		
07:55 25N0		14:	41 25NOV2		וידות :	K:00645 ENG.	baccery			
LINE OPCO							LIST	r NET	TOT	AL
A PERFORM 01-Q PARTS: B PERFORM 99PX PARTS:	TIRE ROTAT 0. * MULT PERF 9	E ROT TE PE 999 00 ***** FORM 999 00	TATION ERFORM TIF CP LABOR: ******** DINT INSPE MULTI POI CP LABOR: *******	32.95 ******* ******* ******** ***********	OTHER ****** CTION OTHER *****	. 0.00	TOTAL 1	**** 0.00 LINE B: ****	32. 0. 0.	
DARTS: 62475 pre	AST R LECTR 70 0. essur syste	EPAI ICAI 00 e te m pa	IR WITH JA CP LABOR: est the co	0.00 0.00 ooling sys pressure ******	OTHER stem an	O.00 od it did no	TOTAL I	0.00 LINE C: the	0.	00
						iding contct				

enroll them in their VIP club. Buyers agree below, buyers give permission to Q/Lane to to receive automated informational, marketing text, emails and phone calls from dealership. Message and data rates may apply.

## DISCLAIMER OF WARRANTIES

Any warranties on the products sold hereby, or used in the repair or service, are those made by the manufacturer. The Dealer hereby expressly disclaims all warranties, either express of implied, including any implied warranty of merchantability or fitness for a particular purpose and the Dealer neither assumes nor authorizes any other person to assume for it any liability in connection with the sale of such products.

I authorize the Dealer to perform the repair or service work described above or to diagnose the problems listed and to perform the appropriate repairs and service. I agree to pay the Dealer the charges for the repair and service work performed to include a shop supply charge for shop supplies, such as fluids, adhesives, cleaners and other expendable items and hazardous waste removal expenses. I agree that the Dealer is not responsible for loss or damage to the Vehicle or articles left in the Vehicle in case of fire, theft or other cause or for any delay in repair caused by the unavailability or delay in delivery of parts. I grant to the Dealer permission to operate the Vehicle on the streets or elsewhere for the purpose of testing and/or inspection. An express mechanics lien is hereby acknowledged on the Vehicle to secure payment of the amount of repair/service

ARBITRATION AGREEMENT

Customer and Dealer agree that all claims, demands, disputes or controversies of every kind or nature that may arise between them concerning or relating to any of the negotiations for and performance of service or repairs to the Vehicle, charges for and adequacy of such service and repairs, and all other aspects of the service and repairs performed on the Vehicle shall be settled by binding arbitration by one arbitrator selected by the Dealer with the consent of the Customer conducted pursuant to the provisions of the Federal Arbitration Act, 9 U.S.C. § 1 et. seq. Either party may demand arbitration by filling a written demand for arbitration with a copy to be served upon the other party. The Customer and Dealer agree

DESCRIPTION	TOTALS
LABOR AMOUNT	32.95
PARTS AMOUNT	0.00
GAS, OIL, LUBE	0.00
SUBLET AMOUNT	0.00
MISC. CHARGES	5.93
TOTAL CHARGES	38.88
LESS INSURANCE	0.00
SALES TAX	0.00
PLEASE PAY THIS AMOUNT	38 88

PARTS AND SERVICE DEPARTMENT HOUSE

			-A-UP					Ford	FORD SERVICE
			MULTI-POINT INSP	PECTION AS RECOM	MENDED BY FORD MOTOR	COMPANY			
		1	RO/Tag#:			ite to vehicle effici	ency and promote a	greener enviror	nment
		,*	Phone#: (	) ::::-	Check and OK at this tim		uire future attention	Requires im	mediate attention
_	rear/Ma	ke/Model:			BODY		===		
CUSTOMER	Odomete	er:	Plate#: Plate#:		8				
MO	Dash Lin	Activation: YES NO OTA Sof	6 U I		EXTERIOR				
IST	Ford	hts: TPMS On TPMS Flashing  This Flashing	Warning Indicator/Messages	☐ ABS ☐	표				
	Ford/Lincol	In Protect (Extended Service Plan): YES NO	NO L Ford Pass / Lincoln Way Member	r ID:	<b>\</b>	\			
ICE	Service	d DUE	Serviced DUE						
MA		☐ THE WORKS	Engine Air F	Filter Ø	· ·	Note any exterior	body damage or defects o	n diagram	
H		Oil Change & Filter	Ø ☐ ☐ Engine Cool		OK FILL	OK FILL		OK FILL	
B		☐ Tire Rotation	Ø ☐ ☐ Transmissio	n Fluid &/or Filter	OK FILL Engine Oil Brake Reservoir		wer Steering		nsmission guipped with dipstick)
2	1	Multi-Point Inspection	☐ ☐ Cabin Air Fil	123330	Brake Reservoir	Wi	ndow Washer		lant Recovery Reservoir
3		Fuel Filter N/A	☐ ☐ Spark Plugs	Ø	Serviced Batte	ry State of Heal	th	Battery	ondition
SCHEDULED MAINTENANCE		K Scheduled Mainte					100%		
S	for vehi	only a partial list maintenance items and is NOT all- icle specific maintenance requirements. N/A is circle	-inclusive. Please consult your Owner's Manual led if certain part Is not applicable.	or visit FordOwner.com	Factory spec cold cran	king amps	(3),000-0	l cold cranking amp	5
PERS	Service		Serviced		Coolin	ng System - Hoses	and Piping		
RING	H블	Horn	Front Wipers Headlights Parking	Rear Wipers (if equipped)	Engin	e Air Filter e Drive Belt(s)			
LIGHTS/HORN/WIPERS			Front Lighting Headlights, Parking 4-Way Flasher	angular, roy clyino,		Air Filter			
3		Rear Lighting - 4-Way Flasher,	Taillights, Stop Lights, Plate Lights				2./27" 44	Less / Less than	3mm
	Serviced	d Tire Tread Depth	7/32" or Greater / Over 5mm		6/32" to 4/32" / 5mm to 3mm	- 16a- T.	The State of the S		Age: *
		Left Front Tire Condition	n:	TPMS Sensor	Sensor Nut/Valve C	ore, eap		Tire PSI:	Age:
		Right Front Tire Condition	on:	TPMS Sensor	Sensor Nut/Valve C	01010-			
TIRES		Left Rear Tire Condition:		TPMS Sensor	Sensor Nut/Valve C		ead Depth: 10		Age:
		Right Rear Tire Condition	n:	TPMS Sensor	Sensor Nut/Valve C	ore/Cap Tr	caa sepiiii   O		Age:
=		7			Sensor Nut/Valve Co	nre/Cap Tr	ead Depth:	Tire PSI:	Age:
		Full Size/Temp Spare Tire	e Condition:	TPMS Sensor	Delisor Maty valve es				
		Full Size/Temp Spare Tire	e Condition:						
		Full Size/Temp Spare Tire	e Condition:	TPMS Sensor  Other/Comm				*Tires sho	uld be replaced after 6 years
		Size:		Other/Comm	ents:	2" (Drum) 3mr		*Tires sho "(Disc) or 1mm or	less or Under 2/32" (Drum)
	Serviced	Size:  Brake Lining 5mm or More or Over	7/32" (Disc) or Over 2mm or 3/32" (Drum)	Other/Comm		2" (Drum) 3mr	n or Less or Under 4/32" Rotor Minimum Spec	*Tires sho "(Disc) or 1mm or	less or Under 2/32" (Drum)
		Size:  Brake Lining Smm or More or Over Left Front Brake	7/32" (Disc) or Over 2mm or 3/32" (Drum) Pad Thickness:	Other/Comm	ents: o 7/32"(Disc) or 1.01 to 2mm or 2/32" to 3/3	2" (Drum) 3mr		*Tires sho "(Disc) or 1mm or l	less or Under 2/32" (Drum)
RAKES	Serviced	Size:  Brake Lining Srom or More or Over Left Front Brake Right Front Brake	7/32" (Disc) or Over 2mm or 3/32" (Drum) Pad Thickness: Pad Thickness:	Other/Comm	ents: o 7/32"(Disc) or 1.01 to 2mm or 2/32" to 3/3 Rotor Actual: Rotor Actual:	2" (Drum) 3mm	Rotor Minimum Spec	*Tires sho (Disc) or 1mm or l C	Less or Under 2/32" (Drum)
RAKES		Size:  Brake Lining 5mm or More or Over Left Front Brake Right Front Brake Left Rear Brake	7/32" (Disc) or Over 2mm or 3/32" (Drum) Pad Thickness: Pad Thickness: Pad/Shoe Thickness:	Other/Comm	ents:  o 7/32" (Disc) or 1.01 to 2mm or 2/32" to 3/3  Rotor Actual:  Rotor Actual:  Rotor/Drum Actual:	2" (Drum) 3mr	Rotor Minimum Spec Rotor Minimum Spec	*Tires sho (Disc) or 1mm or C: :: m Spec:	less or Under 2/32" (Drum)
RAKES	Serviced	Size:  Brake Lining Srom or More or Over Left Front Brake Right Front Brake	7/32" (Disc) or Over 2mm or 3/32" (Drum) Pad Thickness: Pad Thickness:	Other/Comm	ents: o 7/32"(Disc) or 1.01 to 2mm or 2/32" to 3/3 Rotor Actual: Rotor Actual:	2" (Drum) 3mr	Rotor Minimum Spec Rotor Minimum Spec Rotor/Drum Minimui	*Tires sho (Disc) or 1mm or C: :: m Spec:	Less or Under 2/32" (Drum)
RAKES	Serviced	Size:  Brake Lining  Strom or More or Over  Left Front Brake  Right Front Brake  Left Rear Brake  Right Rear Brake	7/32" (Disc) or Over 2mm or 3/32" (Drum) Pad Thickness: Pad Thickness: Pad/Shoe Thickness: Pad/Shoe Thickness:	Other/Comm 3.01 to 4.99mm or 4/32" t	ents:  o 7/32" (Disc) or 1.01 to 2mm or 2/32" to 3/3  Rotor Actual:  Rotor Actual:  Rotor/Drum Actual:	2" (Drum) 3mr	Rotor Minimum Spec Rotor Minimum Spec Rotor/Drum Minimui	*Tires sho (Disc) or 1mm or C: :: m Spec:	Less or Under 2/32" (Drum)
BRAKES	Serviced	Size:  Brake Lining Smm or More or Over Left Front Brake Right Front Brake Left Rear Brake Right Rear Brake Left Front suspension, stru	Pad Thickness:  Pad Thickness:  Pad/Shoe Thickness:  Pad/Shoe Thickness:  Vad/Shoe Thickness:  Pad/Shoe Thickness:	Other/Comm 3.01 to 4.99mm or 4/32* t	ents:  o 7/32" (Disc) or 1.01 to 2mm or 2/32" to 3/3  Rotor Actual:  Rotor Actual:  Rotor/Drum Actual:	2" (Drum) 3mr	Rotor Minimum Spec Rotor Minimum Spec Rotor/Drum Minimui	*Tires sho (Disc) or 1mm or C: :: m Spec:	Less or Under 2/32" (Drum)
BRAKES	Serviced	Size:  Brake Lining 5mm or More or Over Left Front Brake Right Front Brake Right Rear Brake Right Rear Brake Left Front suspension, stru	7/32" (Disc) or Over 2mm or 3/32" (Drum)  Pad Thickness:  Pad Thickness:  Pad/Shoe Thickness:  Pad/Shoe Thickness:  uts, steering linkage, brake lines/hos	3.01 to 4.99mm or 4/32" t	ents:  o 7/32" (Disc) or 1.01 to 2mm or 2/32" to 3/3  Rotor Actual:  Rotor Actual:  Rotor/Drum Actual:	2" (Drum) 3mr	Rotor Minimum Spec Rotor Minimum Spec Rotor/Drum Minimui	*Tires sho (Disc) or 1mm or C: :: m Spec:	Less or Under 2/32" (Drum)
BRAKES	Serviced	Brake Lining  Strim or More or Over  Left Front Brake  Right Front Brake  Right Rear Brake  Left Rear Brake  Right Front suspension, stru  Right Front suspension, stru  Left Rear suspension, sho	Pad Thickness:  Pad/Shoe Thickness:  Pad/Shoe Thickness:  Pad/Shoe Thickness:  Values, steering linkage, brake lines/hosescks/struts, linkage, brake lines/hosescks/struts	3.01 to 4.99mm or 4/32° t  sees Notes:  oses Notes:  Notes:	ents:  o 7/32" (Disc) or 1.01 to 2mm or 2/32" to 3/3  Rotor Actual:  Rotor Actual:  Rotor/Drum Actual:	2" (Drum) 3mr	Rotor Minimum Spec Rotor Minimum Spec Rotor/Drum Minimui	*Tires sho (Disc) or 1mm or C: :: m Spec:	Less or Under 2/32" (Drum)
BRAKES	Serviced	Brake Lining  Strim or More or Over  Left Front Brake  Right Front Brake  Right Rear Brake  Left Rear Brake  Right Front suspension, stru  Right Front suspension, stru  Left Rear suspension, sho	7/32" (Disc) or Over 2mm or 3/32" (Drum)  Pad Thickness:  Pad Thickness:  Pad/Shoe Thickness:  Pad/Shoe Thickness:  uts, steering linkage, brake lines/hos	3.01 to 4.99mm or 4/32° to 4.99m	ents:  o 7/32" (Disc) or 1.01 to 2mm or 2/32" to 3/3  Rotor Actual:  Rotor Actual:  Rotor/Drum Actual:	2" (Drum) 3mr	Rotor Minimum Spec Rotor Minimum Spec Rotor/Drum Minimui	*Tires sho (Disc) or 1mm or C: :: m Spec:	Less or Under 2/32" (Drum)
BRAKES	Serviced	Brake Lining  Strim or More or Over  Left Front Brake  Right Front Brake  Right Rear Brake  Left Rear Brake  Right Front suspension, stru  Right Front suspension, stru  Left Rear suspension, sho	Pad Thickness:  Pad/Shoe Thickness:  Pad/Shoe Thickness:  Pad/Shoe Thickness:  Values, steering linkage, brake lines/hosescks/struts, linkage, brake lines/hosescks/struts	3.01 to 4.99mm or 4/32° to 4.99m	ents:  o 7/32" (Disc) or 1.01 to 2mm or 2/32" to 3/3  Rotor Actual:  Rotor Actual:  Rotor/Drum Actual:	2" (Drum) 3mr	Rotor Minimum Spec Rotor Minimum Spec Rotor/Drum Minimui	*Tires sho (Disc) or 1mm or C: :: m Spec:	Less or Under 2/32" (Drum)
UNDERCARRIAGE BRAKES TI	Serviced	Size:  Brake Lining 5mm or More or Over Left Front Brake Right Front Brake Left Rear Brake Right Rear Brake Right Rear Brake Left Front suspension, structure Right Front suspension, structure Right Front suspension, sho	Pad Thickness:  Pad/Shoe Thickness:  Pad/Shoe Thickness:  Pad/Shoe Thickness:  Values, steering linkage, brake lines/hosescks/struts, linkage, brake lines/hosescks/struts	3.01 to 4.99mm or 4/32° to 4.99m	ents:  o 7/32" (Disc) or 1.01 to 2mm or 2/32" to 3/3  Rotor Actual:  Rotor Actual:  Rotor/Drum Actual:	2" (Drum) 3mr	Rotor Minimum Spec Rotor Minimum Spec Rotor/Drum Minimui	*Tires sho (Disc) or 1mm or C: :: m Spec:	Less or Under 2/32" (Drum)
BRAKES	Serviced	Size:  Brake Lining  Smm or More or Over  Left Front Brake  Right Front Brake  Right Rear Brake  Right Rear Brake  Left Front suspension, structure Right Front suspension, structure Right Rear suspension, sho	Pad Thickness:  Pad Thickness:  Pad/Shoe Thickness:  Pad/Shoe Thickness:  Values, steering linkage, brake lines/hosetruts, steering linkage, brake lines/hosetruts, linkage, brake lines/hoses/struts, linkage, brake lines/hoses/hocks/struts, linkage, brake lines/hoses/hocks/struts/linkage, brake lines/hoses/hocks/struts/linkage, brake lines/hocks/struts/linkage, brake lines/hocks/struts/	3.01 to 4.99mm or 4/32* to 4.99m	ents:  o 7/32" (Disc) or 1.01 to 2mm or 2/32" to 3/3  Rotor Actual:  Rotor Actual:  Rotor/Drum Actual:	2" (Drum) 3mr	Rotor Minimum Spec Rotor Minimum Spec Rotor/Drum Minimu Rotor/Drum Minimur	*Tires sho  (Disc) or 1mm or 1  C:  If m Spec:  In Spec:	ess or Under 2/32" (Drum)  ON  NOTING
BRAKES	Serviced	Size:  Brake Lining  Smm or More or Over  Left Front Brake  Right Front Brake  Right Rear Brake  Right Rear Brake  Left Front suspension, structure Right Front suspension, structure Right Rear suspension, sho	Pad Thickness:  Pad/Shoe Thickness:  Pad/Shoe Thickness:  Pad/Shoe Thickness:  Values, steering linkage, brake lines/hosescks/struts, linkage, brake lines/hosescks/struts	3.01 to 4.99mm or 4/32* to 4.99m	ents:  o 7/32" (Disc) or 1.01 to 2mm or 2/32" to 3/3  Rotor Actual:  Rotor Actual:  Rotor/Drum Actual:	2" (Drum) 3mr	Rotor Minimum Spec Rotor Minimum Spec Rotor/Drum Minimui	*Tires sho (Disc) or 1mm or C: :: m Spec:	Less or Under 2/32" (Drum)
UNDERCARRIAGE BRAKES	Serviced	Size:  Brake Lining	Pad Thickness:  Pad Thickness:  Pad/Shoe Thickness:  Pad/Shoe Thickness:  Values, steering linkage, brake lines/hosetruts, steering linkage, brake lines/hosetruts, linkage, brake lines/hoses/struts, linkage, brake lines/hoses/hocks/struts, linkage, brake lines/hoses/hocks/struts/linkage, brake lines/hoses/hocks/struts/linkage, brake lines/hocks/struts/linkage, brake lines/hocks/struts/	3.01 to 4.99mm or 4/32* to 4.99m	ents:  o 7/32" (Disc) or 1.01 to 2mm or 2/32" to 3/3  Rotor Actual:  Rotor Actual:  Rotor/Drum Actual:	2" (Drum) 3mr	Rotor Minimum Spec Rotor Minimum Spec Rotor/Drum Minimu Rotor/Drum Minimur	*Tires sho  (Disc) or 1mm or 1  C:  If m Spec:  In Spec:	ess or Under 2/32" (Drum)  ON  NOTING
UNDERCARRIAGE BRAKES	Serviced	Size:  Brake Lining	Pad Thickness:  Pad Thickness:  Pad/Shoe Thickness:  Pad/Shoe Thickness:  Values, steering linkage, brake lines/hosetruts, steering linkage, brake lines/hosetruts, linkage, brake lines/hoses/struts, linkage, brake lines/hoses/hocks/struts, linkage, brake lines/hoses/hocks/struts/linkage, brake lines/hoses/hocks/struts/linkage, brake lines/hocks/struts/linkage, brake lines/hocks/struts/	3.01 to 4.99mm or 4/32* to 4.99m	ents:  o 7/32" (Disc) or 1.01 to 2mm or 2/32" to 3/3  Rotor Actual:  Rotor Actual:  Rotor/Drum Actual:	2" (Drum) 3mr	Rotor Minimum Spec Rotor Minimum Spec Rotor/Drum Minimu Rotor/Drum Minimur	*Tires sho  (Disc) or 1mm or 1  C:  If m Spec:  In Spec:	ess or Under 2/32" (Drum)  ON  NOTING
UNDERCARRIAGE	Serviced	Size:  Brake Lining  Smm or More or Over  Left Front Brake  Right Front Brake  Left Rear Brake  Right Rear Brake  Right Front suspension, structure of the suspension, structure of the suspension, should be suspension.  Drivetrain	Pad Thickness:  Pad Thickness:  Pad/Shoe Thickness:  Pad/Shoe Thickness:  Values, steering linkage, brake lines/hosetruts, steering linkage, brake lines/hosetruts, linkage, brake lines/hoses/struts, linkage, brake lines/hoses/hocks/struts, linkage, brake lines/hoses/hocks/struts/linkage, brake lines/hoses/hocks/struts/linkage, brake lines/hocks/struts/linkage, brake lines/hocks/struts/	3.01 to 4.99mm or 4/32* to 4.99m	ents:  o 7/32" (Disc) or 1.01 to 2mm or 2/32" to 3/3  Rotor Actual:  Rotor Actual:  Rotor/Drum Actual:	2" (Drum) 3mr	Rotor Minimum Spec Rotor Minimum Spec Rotor/Drum Minimu Rotor/Drum Minimur	*Tires sho  (Disc) or 1mm or 1  C:  If m Spec:  In Spec:	ess or Under 2/32" (Drum)  ON  NOTING
UNDERCARRIAGE BRAKES	Serviced	Size:  Brake Lining  Smm or More or Over  Left Front Brake  Right Front Brake  Left Rear Brake  Right Rear Brake  Right Front suspension, structure of the suspension, structure of the suspension, should be suspension.  Drivetrain	Pad Thickness:  Pad Thickness:  Pad/Shoe Thickness:  Pad/Shoe Thickness:  Values, steering linkage, brake lines/hosetruts, steering linkage, brake lines/hosetruts, linkage, brake lines/hoses/struts, linkage, brake lines/hoses/hocks/struts, linkage, brake lines/hoses/hocks/struts/linkage, brake lines/hoses/hocks/struts/linkage, brake lines/hocks/struts/linkage, brake lines/hocks/struts/	3.01 to 4.99mm or 4/32* to 4.99m	ents:  o 7/32" (Disc) or 1.01 to 2mm or 2/32" to 3/3  Rotor Actual:  Rotor Actual:  Rotor/Drum Actual:	2" (Drum) 3mr	Rotor Minimum Spec Rotor Minimum Spec Rotor/Drum Minimu Rotor/Drum Minimur	*Tires sho  (Disc) or 1mm or 1  C:  If m Spec:  In Spec:	ess or Under 2/32*(Drum)  NOT INSPECTED  NOT INSPEC
UNDERCARRIAGE BRAKES	Serviced	Size:  Brake Lining  Smm or More or Over  Left Front Brake  Right Front Brake  Left Rear Brake  Right Rear Brake  Right Front suspension, structure of the suspension, structure of the suspension, should be suspension.  Drivetrain	Pad Thickness:  Pad Thickness:  Pad/Shoe Thickness:  Pad/Shoe Thickness:  Values, steering linkage, brake lines/hosetruts, steering linkage, brake lines/hosetruts, linkage, brake lines/hoses/struts, linkage, brake lines/hoses/hocks/struts, linkage, brake lines/hoses/hocks/struts/linkage, brake lines/hoses/hocks/struts/linkage, brake lines/hocks/struts/linkage, brake lines/hocks/struts/	3.01 to 4.99mm or 4/32* to 4.99m	ents:  o 7/32" (Disc) or 1.01 to 2mm or 2/32" to 3/3  Rotor Actual:  Rotor Actual:  Rotor/Drum Actual:	2" (Drum) 3mr	Rotor Minimum Spec Rotor Minimum Spec Rotor/Drum Minimu Rotor/Drum Minimur	*Tires sho  (Disc) or 1mm or 1  C:  If m Spec:  In Spec:	ess or Under 2/32" (Drum)  ON  NOTING
UNDERCARRIAGE BRAKES	Serviced	Size:  Brake Lining 5mm or More or Over Left Front Brake Right Front Brake Left Rear Brake Right Rear Brake Right Rear Brake Left Front suspension, structure Right Front suspension, structure Right Rear suspension, sho	Pad Thickness:  Pad Thickness:  Pad/Shoe Thickness:  Pad/Shoe Thickness:  Values, steering linkage, brake lines/hosetruts, steering linkage, brake lines/hosetruts, linkage, brake lines/hoses/struts, linkage, brake lines/hoses/hocks/struts, linkage, brake lines/hoses/hocks/struts/linkage, brake lines/hoses/hocks/struts/linkage, brake lines/hocks/struts/linkage, brake lines/hocks/struts/	3.01 to 4.99mm or 4/32* to 4.99m	ents:  o 7/32" (Disc) or 1.01 to 2mm or 2/32" to 3/3  Rotor Actual:  Rotor Actual:  Rotor/Drum Actual:	2" (Drum) 3mr	Rotor Minimum Spec Rotor Minimum Spec Rotor/Drum Minimu Rotor/Drum Minimur	*Tires sho  (Disc) or 1mm or 1  C:  If m Spec:  In Spec:	ess or Under 2/32" (Drum)  ON  NOTING
UNDERCARRIAGE BRAKES	Serviced	Size:  Brake Lining 5mm or More or Over Left Front Brake Right Front Brake Left Rear Brake Right Rear Brake Right Rear Brake Left Front suspension, structure Right Front suspension, structure Right Rear suspension, sho	Pad Thickness:  Pad Thickness:  Pad/Shoe Thickness:  Pad/Shoe Thickness:  Values, steering linkage, brake lines/hosetruts, steering linkage, brake lines/hosetruts, linkage, brake lines/hoses/struts, linkage, brake lines/hoses/hocks/struts, linkage, brake lines/hoses/hocks/struts/linkage, brake lines/hoses/hocks/struts/linkage, brake lines/hocks/struts/linkage, brake lines/hocks/struts/	3.01 to 4.99mm or 4/32* to 4.99m	ents:  o 7/32" (Disc) or 1.01 to 2mm or 2/32" to 3/3  Rotor Actual:  Rotor Actual:  Rotor/Drum Actual:	2" (Drum) 3mr	Rotor Minimum Spec Rotor Minimum Spec Rotor/Drum Minimu Rotor/Drum Minimur	*Tires sho  (Disc) or 1mm or 1  C:  If m Spec:  In Spec:	ess or Under 2/32" (Drum)  ON  NOTING
UNDERCARRIAGE BRAKES	Serviced	Size:  Brake Lining 5mm or More or Over Left Front Brake Right Front Brake Left Rear Brake Right Rear Brake Right Rear Brake Left Front suspension, structure Right Front suspension, structure Right Rear suspension, sho	Pad Thickness:  Pad Thickness:  Pad/Shoe Thickness:  Pad/Shoe Thickness:  Values, steering linkage, brake lines/hosetruts, steering linkage, brake lines/hosetruts, linkage, brake lines/hoses/struts, linkage, brake lines/hoses/hocks/struts, linkage, brake lines/hoses/hocks/struts/linkage, brake lines/hoses/hocks/struts/linkage, brake lines/hocks/struts/linkage, brake lines/hocks/struts/	3.01 to 4.99mm or 4/32* to 4.99m	ents:  o 7/32" (Disc) or 1.01 to 2mm or 2/32" to 3/3  Rotor Actual:  Rotor Actual:  Rotor/Drum Actual:	2° (Drum) 3mr	Rotor Minimum Spec Rotor Minimum Spec Rotor/Drum Minimu Rotor/Drum Minimur	*Tires sho  (Disc) or 1mm or 1  C:  If m Spec:  In Spec:	ess or Under 2/32" (Drum)  ON  NOTING
UNDERCARRIAGE BRAKES	Serviced	Size:  Brake Lining 5mm or More or Over Left Front Brake Right Front Brake Left Rear Brake Right Rear Brake Right Rear Brake Left Front suspension, structure Right Front suspension, structure Right Rear suspension, sho	Pad Thickness:  Pad Thickness:  Pad/Shoe Thickness:  Pad/Shoe Thickness:  Values, steering linkage, brake lines/hosetruts, steering linkage, brake lines/hosetruts, linkage, brake lines/hoses/struts, linkage, brake lines/hoses/hocks/struts, linkage, brake lines/hoses/hocks/struts/linkage, brake lines/hoses/hocks/struts/linkage, brake lines/hocks/struts/linkage, brake lines/hocks/struts/	3.01 to 4.99mm or 4/32* to 4.99m	ents:  o 7/32" (Disc) or 1.01 to 2mm or 2/32" to 3/3  Rotor Actual:  Rotor Actual:  Rotor/Drum Actual:	2" (Drum) 3mr	Rotor Minimum Spec Rotor Minimum Spec Rotor/Drum Minimu Rotor/Drum Minimur	*Tires sho  (Disc) or 1mm or 1  C:  If m Spec:  In Spec:	ess or Under 2/32" (Drum)  ON  NOTING
UNDERCARNAGE BRAKES	Serviced	Size:  Brake Lining	Pad Thickness:  Pad Thickness:  Pad/Shoe Thickness:  Description  Description  Description	3.01 to 4.99mm or 4/32* to 4.99m	ents:  o 7/32" (Disc) or 1.01 to 2mm or 2/32" to 3/3 Rotor Actual: Rotor/Drum Actual: Rotor/Drum Actual:	2° (Drum) 3mr	Rotor Minimum Spec Rotor Minimum Spec Rotor/Drum Minimu Rotor/Drum Minimur	*Tires sho  (Disc) or 1mm or 1  C:  If m Spec:  In Spec:	ess or Under 2/32" (Drum)  ON  NOTING
UNDERCARNAGE BRAKES	Serviced	Size:  Brake Lining	Pad Thickness:  Pad Thickness:  Pad/Shoe Thickness:  Description  Description  Description	3.01 to 4.99mm or 4/32* to 4.99m	ents:  o 7/32" (Disc) or 1.01 to 2mm or 2/32" to 3/3 Rotor Actual: Rotor/Drum Actual: Rotor/Drum Actual:	2° (Drum) 3mr	Rotor Minimum Spec Rotor Minimum Spec Rotor/Drum Minimur Rotor/Drum Minimur	*Tires sho  (Disc) or 1mm or  c: :: m Spec: n Spec:	TOTAL ESTIMATE
UNDERCARRIAGE BRAKES	Serviced	Size:  Brake Lining	Pad Thickness:  Pad Thickness:  Pad/Shoe Thickness:  Description  Description  Description	3.01 to 4.99mm or 4/32* to 4.99m	ents:  o 7/32" (Disc) or 1.01 to 2mm or 2/32" to 3/3 Rotor Actual: Rotor/Drum Actual: Rotor/Drum Actual:	2° (Drum) 3mr	Rotor Minimum Spec Rotor Minimum Spec Rotor/Drum Minimur Rotor/Drum Minimur	*Tires sho  (Disc) or 1mm or  c: :: m Spec: n Spec:	ess or Under 2/32" (Drum)  ON  NOT INSPECTED  ON  ON  ON  ON  ON  ON  ON  ON  ON  O