


**Accessory: Whole Home Backup (WHB)**
**Features:**

- Whole home backup when paired with Delta E series storage system
- Intelligent grid disconnect via 200A electronic relay
- Indoor or outdoor rated with type 3R protection
- Maximum 22kA input short circuit current protection paired with a 22kA interrupting rating MCCB
- Supports AC-coupled Delta E series storage system
- With minimal installation time and cost savings

<b>Model Name</b>	WHB-200
<b>CONNECTION TO UTILITY GRID AND HOUSEHOLD DISTRIBUTION</b>	
Rated grid voltage	240 V
Output nom. voltage of line conductor	240/120V
Rated power frequency	60 Hz
Maximum input and output current	200 A
Charge battery from AC (if allowed)	Yes
Typical nighttime power consumption	<5 W
<b>AUTO TRANSFOMER</b>	
Maximum imbalance current	30 A
Automatic switchover time	<5 Sec
Typical nighttime power consumption	<5 W
<b>GENERAL SPECIFICATION</b>	
Grid configurations	240V:120V split-phase system
Operating temperature range	-13 °F to 122 °F (-25°C ~ 50°C)
Humidity	0% ~ 95%
Maximum operating altitude	9,843 ft (3,000m) above sea level
<b>MECHANICAL DESIGN</b>	
Size L x W x D inches ( L x W x D )	15.7 x 20.3 x 7.9 in (398 x 515 x 200 mm)
Weight	48 lb (21.8 kg)
Installation	Wall Mounting
<b>STANDARDS / DIRECTIVES</b>	
Enclosure Protection Rating	Type 3R
Safety	UL 1741, CSA-C22.2 No. 107.1-01